

ニカド電池 (一部)

	品番	公称電圧 (V)	公称容量 (mAh)	寸法		標準充電		急速充電		質量 (約g)
				直径(mm)	高さ(mm)	電流(mA)	時間(h)	電流(mA)	時間(h)	
単4	AAA250	1.2	250	10.5	44.5	25	15	250	1.4	11
	AAA400	1.2	400	10.5	44.5	40	15	400	1.4	13
	2/3AA400	1.2	400	14.5	29.0	40	15	400	1.4	14
単3	4/5AA700	1.2	700	14.5	43.0	70	15	700	1.4	20
	AA600	1.2	600	14.5	50.5	60	15	600	1.4	22
	AA1000	1.2	1000	14.5	50.5	100	15	1000	1.4	24
	4/3AA1200	1.2	1200	14.5	65.5	120	15	1200	1.4	31
	2/3A600	1.2	600	17.0	28.0	60	15	600	1.4	20
A	4/5A1200	1.2	1200	17.0	43.0	120	15	1200	1.4	27
	A1400	1.2	1400	17.0	50.0	140	15	1400	1.4	32
Sub-C	2/3SC700	1.2	700	23.0	26.5	70	15	700	1.4	25
	4/5SC1200	1.2	1200	23.0	34.0	120	15	1200	1.4	41
	SC1300	1.2	1300	23.0	43.0	130	15	1300	1.4	48
	SC2100	1.2	2100	23.0	43.0	210	15	2100	1.4	50
単2	C1200	1.2	1200	25.8	51.0	120	15	1200	1.4	53
	C3000	1.2	3000	25.8	51.0	300	15	3000	1.4	75
単1	D1200	1.2	1200	33.0	61.5	120	15	1200	1.4	66
	D5000	1.2	5000	33.0	61.5	500	15	5000	1.4	145
F	F8000	1.2	8000	33.0	90.5	900	15	8000	1.4	200

市販ニッケル水素電池

サイズ	公称電圧 (V)	公称容量 (mAh)	標準充電		急速充電		サイズ (mm)	質量 (約g)
			電流(mA)	時間(h)	電流(mA)	時間(h)		
単1(D)	1.2	8500	850	15	8500	1.2	Φ32.2*61.5	165
単2(C)	1.2	4500	450	15	4500	1.2	Φ25.5*49.0	87
単3(AA)	1.2	2700	270	15	2700	1.2	Φ14.3*50.5	30
単4(AAA)	1.2	1100	110	15	1100	1.2	Φ10.3*44.5	12.5
9V(006P)	8.4	220	22	15	220	1.2	47*25*16	45.0

ニッケル水素電池リスト (一部)

	品番	公称電圧 (V)	公称容量 (mAh)	寸法		標準充電		急速充電		質量 (約g)
				直径(mm)	高さ(mm)	電流(mA)	時間(h)	電流(mA)	時間(h)	
AAAA	AAAA	1.2	300	8.4	43.5	30	15	300	1.2	8.5
単4	1/3AAA120	1.2	120	10.5	15.0	12	15	120	1.2	6
	2/3AAA300	1.2	300	10.5	29.0	28	15	300	1.2	8
	AAA600	1.2	600	10.5	44.5	60	15	600	1.2	12
	AAA950	1.2	950	10.5	44.5	95	15	950	1.2	14
	5/4AAA700	1.2	700	10.5	50.5	70	15	700	1.2	13
	5/3AAA900	1.2	900	10.5	66.5	90	15	900	1.2	18
	5/3AAA1000	1.2	1000	10.5	66.5	100	15	1000	1.2	18
単3	1/2AA600	1.2	600	14.5	24.0	60	15	600	1.2	13
	2/3AA700	1.2	700	14.5	29.0	70	15	700	1.2	14
	4/5AA1200	1.2	1200	14.5	43.0	120	15	1200	1.2	23
	AA1200	1.2	1200	14.5	50.5	120	15	1200	1.2	25
	AA2000	1.2	2000	14.5	50.5	200	15	2000	1.2	29
	AA2500	1.2	2500	14.5	50.5	250	15	1250	2.2	30
	4/3AA2200	1.2	2200	14.5	67.0	220	15	2200	1.2	33
	2/3A1100	1.2	1100	17.0	28.0	110	15	1100	1.2	21
A	4/5A1900	1.2	1900	17.0	43.0	190	15	1900	1.2	33
	A2100	1.2	2100	17.0	50.0	210	15	2100	1.2	36
	A2300	1.2	2300	17.0	50.0	230	15	2300	1.2	38
	4/3A3600	1.2	3600	17.0	67.0	360	15	3600	1.2	47
Sub-C	SC2500	1.2	2500	23.0	43.0	250	15	2500	1.2	58
	SC3300	1.2	3300	23.0	43.0	330	15	3300	1.2	62
単2	C4500	1.2	4500	25.8	51.0	450	15	4500	1.2	77
単1	D8000	1.2	8000	33.0	61.8	800	15	8000	1.2	170
	D9000	1.2	9000	33.0	61.8	900	15	9000	1.2	175
F	F14000	1.2	14000	33.0	90.5	1400	15	14000	1.2	230

リチウムイオン電池リスト (一部)

形	品番	公称電圧 (V)	容量(mAh)		寸法(mm)		質量 (約g)
			公称	最小	直径	高さ	
円柱形	14500	3.7	750	720	14.5	50.0	18
	14650	3.7	1100	1050	14.5	65.0	24
	17335	3.7	700	650	16.8	34.5	18
	17500	3.7	1100	1050	16.8	50.0	27
	18490	3.7	1400	1350	18.1	49.0	33
	18650	3.7	1800	2150	18.1	65.0	43
	18650	3.7	2200	2150	18.1	65.0	45
	LIR1620	3.7	10	8	16.0	3.2	1.2
ボタン式	LIR2016	3.7	12	10	20.0	1.9	1.6
	LIR2025	3.7	30	25	20.0	2.8	2.2
	LIR2032	3.7	40	35	29.0	3.4	2.5
	LIR2430	3.7	60	55	24.5	3.3	3.7
	LIR1620	3.7	120	100	24.5	5.3	5.5
	LIR1620	3.7	160	150	24.5	8.0	7.0

リチウムイオンポリマー電池リスト (一部)

形	品番	公称電圧 (V)	容量(mAh)		寸法(mm)		質量 (約g)
			公称	最小	厚さ×巾×長さ	質量 (約g)	
アルミニウム 四角型 外装フィルム	361131	3.7	85	75	3.6×11×31	1.8	
	061148	3.7	230	215	6.0×11×48	4.5	
	061225	3.7	120	110	6.0×12×25	2.7	
	481229	3.7	130	115	4.8×12×29	2.7	
	551230	3.7	140	130	5.5×12×30	3.0	
	061235	3.7	190	170	6.0×12×35	4.3	
	551429	3.7	200	180	5.5×14×29	4.1	
	111435	3.7	340	330	11×14×35	6.8	
	082890	3.7	2000	1950	8.0×28×90	38.5	
	552927	3.7	280	260	5.5×29×27	5.8	
	062937	3.7	600	580	6.0×29×27	11.5	
	1029102	3.7	3100	3200	10×29×102	62.5	
	553040	3.7	600	580	5.5×30×40	12.2	
	103048	3.7	1500	1400	10×30×48	29.0	